

工博士两指平动式夹爪



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-P40A-1	2.5	123/132	0.08	0.68	50	0.1	0.01	40
GBS-04-P40A-1-AS	2.5	163/-	0.09	0.68	45	0.1	0.01	40
GBS-04-P40A-1-IS	25	-/182	0.09	0.68	45	0.1	0.01	40
GBS-04-P40A-1-SD	25	123/132	0.11	0.68	50	0.1	0.01	64
GBS-04-P40A-1-AS-SD	25	163/-	0.11	0.68	45	0.1	0.01	64
GBS-04-P40A-1-IS-SD	2.5	-/182	0.11	0.68	45	0.1	0.01	64
GBS-04-P40A-1-TEM	25	123/132	0.08	0.68	50	0.1	0.01	40
GBS-04-P40A-1-AS-TEM	25	163/-	0.09	0.68	45	0.1	0.01	40
GBS-04-P40A-1-IS-TEM	25	-/182	0.09	0.68	45	0.1	0.01	40
GBS-04-P50A-1	4	140/145	0.15	0.77	64	0.18	0.01	40
GBS-04-P50A-2	2	290/310	0.15	1.6	58	0.18	0.01	40
GBS-04-P50A-1-AS	4	185/-	0.2	0.77	58	0.18	0.01	40
GBS-04-P50A-2-AS	2	385/-	0.2	1.6	50	0.18	0.01	40
GBS-04-P50A-1-IS	4	-/190	0.2	0.77	58	0.18	0.01	40
GBS-04-P50A-2-IS	2	-/405	0.2	1.6	50	0.18	0.01	40
GBS-04-P50A-1-SD	4	140/145	0.18	0.77	64	0.18	0.01	64
GBS-04-P50A-2-SD	2	290/310	0.18	1.6	58	0.18	0.01	64
GBS-04-P50A-1-AS-SD	4	185/-	0.23	0.77	58	0.18	0.01	64
GBS-04-P50A-2-AS-SD	2	385/-	0.23	1.6	50	0.18	0.01	64
GBS-04-P50A-1-IS-SD	4	-/190	0.23	0.77	58	0.18	0.01	64
GBS-04-P50A-2-IS-SD	2	-/405	0.23	1.6	50	0.18	0.01	64
GBS-04-P50A-1-TEM	4	140/145	0.15	0.77	64	0.18	0.01	40

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量kg	重复定位精度mm	IP等级
GBS-04-P50A-2-TEM	2	290/310	0.15	1.6	58	0.18	0.01	40
GBS-04-P50A-1-AS-TEM	4	185/-	0.2	0.77	58	0.18	0.01	40
GBS-04-P50A-2-AS-TEM	2	385/-	0.2	1.6	50	0.18	0.01	40
GBS-04-P50A-1-IS-TEM	4	-/190	0.2	0.77	58	0.18	0.01	40
GBS-04-P50A-2-IS-TEM	2	-/405	0.2	1.6	50	0.18	0.01	40
GBS-04-P64A-1	6	250/270	0.28	1.38	80	0.35	0.01	40
GBS-04-P64A-2	3	520/565	0.28	2.86	72	0.35	0.01	40
GBS-04-P64A-1-AS	6	340/-	0.37	1.38	72	0.35	0.01	40
GBS-04-P64A-2-AS	3	710/-	0.37	2.86	64	0.35	0.01	40
GBS-04-P64A-1-IS	6	-/360	0.37	1.38	72	0.35	0.01	40
GBS-04-P64A-2-IS	3	-/755	0.37	2.86	64	0.35	0.01	40
GBS-04-P64A-1-SD	6	250/270	0.35	1.38	80	0.35	0.01	64
GBS-04-P64A-2-SD	3	520/565	0.35	2.86	72	0.35	0.01	64
GBS-04-P64A-1-AS-SD	6	340/-	0.44	1.38	72	0.35	0.01	64
GBS-04-P64A-2-AS-SD	3	710/-	0.44	2.86	64	0.35	0.01	64
GBS-04-P64A-1-IS-SD	6	-/360	0.44	1.38	72	0.35	0.01	64
GBS-04-P64A-2-IS-SD	3	-/755	0.44	2.86	64	0.35	0.01	64
GBS-04-P64A-1-TEM	6	250/270	0.28	1.38	80	0.35	0.01	40
GBS-04-P64A-2-TEM	3	520/565	0.28	2.86	72	0.35	0.01	40
GBS-04-P64A-1-AS-TEM	6	340/-	0.37	1.38	72	0.35	0.01	40
GBS-04-P64A-2-AS-TEM	3	710/-	0.37	2.86	64	0.35	0.01	40
GBS-04-P64A-1-IS-TEM	6	-/360	0.37	1.38	72	0.35	0.01	40
GBS-04-P64A-2-IS-TEM	3	-/755	0.37	2.86	64	0.35	0.01	40
GBS-04-P80A-1	8	415/465	0.5	2.31	100	0.6	0.01	40
GBS-04-P80A-2	4	860/960	0.5	4.73	90	0.6	0.01	40

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-P80A-1-AS	8	570/-	0.6	2.31	90	0.6	0.01	40
GBS-04-P80A-2-AS	4	1180/-	0.6	4.73	80	0.6	0.01	40
GBS-04-P80A-1-IS	8	-/620	0.6	2.31	90	0.6	0.01	40
GBS-04-P80A-2-IS	4	-/1280	0.6	4.73	80	0.6	0.01	40
GBS-04-P80A-1-SD	8	415/465	0.6	2.31	100	0.6	0.01	64
GBS-04-P80A-2-SD	4	860/960	0.6	4.73	90	0.6	0.01	64
GBS-04-P80A-1-AS-SD	8	570/-	0.7	2.31	90	0.6	0.01	64
GBS-04-P80A-2-AS-SD	4	1180/-	0.7	4.73	80	0.6	0.01	64
GBS-04-P80A-1-IS-SD	8	-/620	0.7	2.31	90	0.6	0.01	64
GBS-04-P80A-2-IS-SD	4	-/1280	0.7	4.73	80	0.6	0.01	64
GBS-04-P80A-1-TEM	8	415/465	0.5	2.31	100	0.6	0.01	40
GBS-04-P80A-2-TEM	4	860/960	0.5	4.73	90	0.6	0.01	40
GBS-04-P80A-1-AS-TEM	8	570/-	0.6	2.31	90	0.6	0.01	40
GBS-04-P80A-2-AS-TEM	4	1180/-	0.6	4.73	80	0.6	0.01	40
GBS-04-P80A-1-IS-TEM	8	-/620	0.6	2.31	90	0.6	0.01	40
GBS-04-P80A-2-IS-TEM	4	-/1280	0.6	4.73	80	0.6	0.01	40
GBS-04-P100A-1	10	660/725	0.81	3.63	125	11	0.01	40
GBS-04-P100A-2	5	1370/1500	0.81	7.54	115	11	0.01	40
GBS-04-P100A-1-AS	10	900/-	1	3.63	115	1.1	0.01	40
GBS-04-P100A-2-AS	5	1870/-	1	7.54	100	1.1	0.01	40
GBS-04-P100A-1-IS	10	-/965	1	3.63	115	1.1	0.01	40
GBS-04-P100A-2-IS	5	-/2000	1	7.54	100	1.1	0.01	40
GBS-04-P100A-1-SD	10	660/725	0.99	3.63	125	11	0.01	64
GBS-04-P100A-2-SD	5	1370/1500	0.99	7.54	115	1.1	0.01	64
GBS-04-P100A-1-AS-SD	10	900/-	1.18	3.63	115	1.1	0.01	64

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量kg	重复定位精度mm	IP等级
GBS-04-P100A-2-AS-SD	5	1870/-	118	7.54	100	1.1	0.01	64
GBS-04-P100A-1-IS-SD	10	-/965	1.18	3.63	115	11	0.01	64
GBS-04-P100A-2-IS-SD	5	-/2000	1.18	7.54	100	1.1	0.01	64
GBS-04-P100A-1-TEM	10	660/725	0.81	3.63	125	1.1	0.01	40
GBS-04-P100A-2-TEM	5	1370/1500	0.81	7.54	115	1.1	0.01	40
GBS-04-P100A-1-AS-TEM	10	900/-	1	3.63	115	1.1	0.01	40
GBS-04-P100A-2-AS-TEM	5	1870/-	1	7.54	100	1.1	0.01	40
GBS-04-P100A-1-IS-TEM	10	-/965	1	3.63	115	1.1	0.01	40
GBS-04-P100A-2-IS-TEM	5	-/2000	1	7.54	100	1.1	0.01	40
GBS-04-P110A-1	20	1050/1150	2	5.25	150	2	0.01	40
GBS-04-P125A-1	13	1080/1170	1.35	594	160	2.1	0.01	40
GBS-04-P125A-2	6	2240/2420	1.35	12.32	145	2.1	0.01	40
GBS-04-P125A-1-AS	13	1470/-	1.85	5.94	145	2.1	0.01	40
GBS-04-P125A-2-AS	6	3040/-	1.85	12.32	125	2.1	0.01	40
GBS-04-P125A-1-IS	13	-/1560	1.85	5.94	145	2.1	0.01	40
GBS-04-P125A-2-IS	6	-/3220	1.85	12.32	125	2.1	0.01	40
GBS-04-P125A-1-SD	13	1080/1170	1.55	5.94	160	2.1	0.01	64
GBS-04-P125A-2-SD	6	2240/2420	1.55	12.32	145	2.1	0.01	64
GBS-04-P125A-1-AS-SD	13	1470/-	2.05	5.94	145	2.1	0.01	64
GBS-04-P125A-2-AS-SD	6	3040/-	2.05	12.32	125	2.1	0.01	64
GBS-04-P125A-1-IS-SD	13	-/1560	2.05	5.94	145	2.1	0.01	64
GBS-04-P125A-2-IS-SD	6	-/3220	2.05	12.32	125	2.1	0.01	64
GBS-04-P125A-1-TEM	13	1080/1170	1.35	594	160	2.1	0.01	40
GBS-04-P125A-2-TEM	6	2240/2420	1.35	12.32	145	2.1	0.01	40
GBS-04-P125A-1-AS-TEM	13	1470/-	1.85	5.94	145	2.1	0.01	40

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-P125A-2-AS-TEM	6	3040/-	1.85	12.32	125	21	0.01	40
GBS-04-P125A-1-IS-TEM	13	-/1560	1.85	594	145	2.1	0.01	40
GBS-04-P125A-2-IS-TEM	6	-/3220	1.85	12.32	125	21	0.01	40
GBS-04-P160A-1	16	1640/1770	2.6	9.02	200	3.5	0.01	40
GBS-04-P160A-2	8	3200/3460	2.6	17.6	190	35	0.01	40
GBS-04-P160A-1-AS	16	2210/-	3.3	9.02	180	35	0.01	40
GBS-04-P160A-2-AS	8	4420/-	3.3	17.6	170	35	0.01	40
GBS-04-P160A-1-IS	16	-/2340	3.3	9.02	180	35	0.01	40
GBS-04-P160A-2-IS	8	-/4680	3.6	17.6	170	3.5	0.01	40
GBS-04-P160A-1-SD	16	1640/1770	3	9.02	200	3.5	0.01	64
GBS-04-P160A-2-SD	8	3200/3460	3	17.6	190	3.5	0.01	64
GBS-04-P160A-1-AS-SD	16	2210/-	4	9.02	180	3.5	0.01	64
GBS-04-P160A-2-AS-SD	8	4420/-	4	17.6	170	3.5	0.01	64
GBS-04-P160A-1-IS-SD	16	-/2340	4	9.02	180	35	0.01	64
GBS-04-P160A-2-IS-SD	8	-/4680	4	17.6	170	3.5	0.01	64
GBS-04-P160A-1-TEM	16	1640/1770	2.6	9.02	200	3.5	0.01	40
GBS-04-P160A-2-TEM	8	3200/3460	2.6	17.6	190	35	0.01	40
GBS-04-P160A-1-AS-TEM	16	2210/-	3.3	9.02	180	35	0.01	40
GBS-04-P160A-2-AS-TEM	8	4420/-	3.3	17.6	170	35	0.01	40
GBS-04-P160A-1-IS-TEM	16	-/2340	3.3	9.02	180	3.5	0.01	40
GBS-04-P160A-2-IS-TEM	8	-/4680	3.6	17.6	170	35	0.01	40
GBS-04-P200A-1	25	2700/2870	5.2	14.85	240	65	0.02	40
GBS-04-P200A-1-AS	25	3610/-	7	14.85	220	6.5	0.02	40
GBS-04-P200A-1-IS	25	-/3780	7	14.85	220	6.5	0.02	40
GBS-04-P200A-1-SD	25	2700/2870	5.8	14.85	240	6.5	0.02	64

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-P200A-1-AS-SD	25	3610/-	7.6	14.85	220	6.5	0.02	64
GBS-04-P200A-1-IS-SD	25	-/3780	7.6	14.85	220	65	0.02	64
GBS-04-P200A-1-TEM	25	2700/2870	5.2	14.85	240	6.5	0.02	40
GBS-04-P200A-1-AS-TEM	25	3610/-	7	14.85	220	6.5	0.02	40
GBS-04-P200A-1-IS-TEM	25	-/3780	7	14.85	220	6.5	0.02	40
GBS-04-P240A-1	30	4200/4440	8	21.5	280	8.5	0.04	40
GBS-04-P240A-1-AS	30	5300/-	11.5	21.5	260	8.5	0.04	40
GBS-04-P240A-1-IS	30	-/5540	11.5	21.5	260	85	0.04	40
GBS-04-P240A-1-SD	30	4200/4440	11	21.5	280	8.5	0.04	64
GBS-04-P240A-1-AS-SD	30	5300/-	145	21.5	260	8.5	0.04	64
GBS-04-P240A-1-IS-SD	30	-/5540	145	21.5	260	8.5	0.04	64
GBS-04-P240A-1-TEM	30	4200/4440	8	21.5	280	8.5	0.04	40
GBS-04-P240A-1-AS-TEM	30	5300/-	11.5	21.5	260	8.5	0.04	40
GBS-04-P240A-1-IS-TEM	30	-/5540	11.5	21.5	260	8.5	0.04	40
GBS-04-P300A-1	35	6000/6260	13.5	33	300	11.5	0.05	40
GBS-04-P300A-1-AS	35	7400/-	175	33	270	11.5	0.05	40
GBS-04-P300A-1-IS	35	-/7660	175	33	270	115	0.05	40
GBS-04-P300A-1-SD	35	6000/6260	175	33	300	115	0.05	64
GBS-04-P300A-1-AS-SD	35	7400/-	215	33	270	115	0.05	64
GBS-04-P300A-1-IS-SD	35	-/7660	21.5	33	270	11.5	0.05	64
GBS-04-P300A-1-TEM	35	6000/6260	13.5	33	300	11.5	0.05	40

工博士三指定心式夹爪



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-C40A-1	2.5	255/270	0.12	1.38	50	0.1	0.01	40
GBS-04-C40A-1-AS	2.5	355/-	0.15	1.38	45	0.1	0.01	40
GBS-04-C40A-1-IS	2.5	-/370	0.15	1.38	45	0.1	0.01	40
GBS-04-C40A-1-SD	2.5	255/270	0.15	1.38	50	0.1	0.01	64
GBS-04-C40A-1-AS-SD	2.5	355/-	0.18	1.38	45	0.1	0.01	64
GBS-04-C40A-1-IS-SD	2.5	-/370	0.18	1.38	45	0.1	0.01	64
GBS-04-C40A-1-TEM	2.5	255/270	0.12	1.38	50	0.1	0.01	40
GBS-04-C40A-1-AS-TEM	2.5	355/-	0.15	1.38	45	0.1	0.01	40
GBS-04-C40A-1-IS-TEM	2.5	-/370	0.15	1.38	45	0.1	0.01	40
GBS-04-C50A-1	4	325/355	0.25	1.76	64	0.18	0.01	40
GBS-04-C50A-1-AS	4	445/-	0.3	1.76	58	0.18	0.01	40
GBS-04-C50A-1-IS	4	-/505	0.3	1.76	58	0.18	0.01	40
GBS-04-C50A-1-SD	4	325/355	0.31	1.76	64	0.18	0.01	64
GBS-04-C50A-1-AS-SD	4	445/-	0.36	1.76	58	0.18	0.01	64
GBS-04-C50A-1-IS-SD	4	-/505	0.36	1.76	58	0.18	0.01	64
GBS-04-C50A-1-TEM	4	325/355	0.25	1.76	64	0.18	0.01	40
GBS-04-C50A-1-AS-TEM	4	445/-	0.3	1.76	58	0.18	0.01	40
GBS-04-C50A-1-IS-TEM	4	-/505	0.3	1.76	58	0.18	0.01	40
GBS-04-C64A-1	6	580/640	0.43	3.19	80	0.35	0.01	40
GBS-04-C64A-1-AS	6	765/-	0.54	3.19	72	0.35	0.01	40
GBS-04-C64A-1-IS	6	-/860	0.54	3.19	72	0.35	0.01	40
GBS-04-C64A-1-SD	6	580/640	0.6	3.19	80	0.35	0.01	64

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量kg	重复定位精度mm	IP等级
GBS-04-C64A-1-AS-SD	6	765/-	0.71	3.19	72	0.35	0.01	64
GBS-04-C64A-1-IS-SD	6	-/860	0.71	3.19	72	0.35	0.01	64
GBS-04-C64A-1-TEM	6	580/640	0.43	3.19	80	0.35	0.01	40
GBS-04-C64A-1-AS-TEM	6	765/-	0.54	3.19	72	0.35	0.01	40
GBS-04-C64A-1-IS-TEM	6	-/860	0.54	3.19	72	0.35	0.01	40
GBS-04-C80A-1	8	1000/1080	0.79	5.5	100	0.6	0.01	40
GBS-04-C80A-1-AS	8	1350/-	0.96	5.5	90	0.6	0.01	40
GBS-04-C80A-1-IS	8	-/1450	0.96	5.5	90	0.6	0.01	40
GBS-04-C80A-1-SD	8	1000/1080	1	5.5	100	0.6	0.01	64
GBS-04-C80A-1-AS-SD	8	1350/-	1.17	5.5	90	0.6	0.01	64
GBS-04-C80A-1-IS-SD	8	-/1450	1.17	5.5	90	0.6	0.01	64
GBS-04-C80A-1-TEM	8	1000/1080	0.79	5.5	100	0.6	0.01	40
GBS-04-C80A-1-AS-TEM	8	1350/-	0.96	5.5	90	0.6	0.01	40
GBS-04-C80A-1-IS-TEM	8	-/1450	0.96	5.5	90	0.6	0.01	40
GBS-04-C100A-1	10	1800/1920	1.41	9.9	125	1.1	0.01	40
GBS-04-C100A-1-AS	10	2520/-	1.95	9.9	115	1.1	0.01	40
GBS-04-C100A-1-IS	10	-/2700	1.95	9.9	115	1.1	0.01	40
GBS-04-C100A-1-SD	10	1800/1920	1.9	9.9	125	1.1	0.01	64
GBS-04-C100A-1-AS-SD	10	2520/-	2.44	9.9	115	1.1	0.01	64
GBS-04-C100A-1-IS-SD	10	-/2700	2.44	9.9	115	1.1	0.01	64
GBS-04-C100A-1-TEM	10	1800/1920	1.41	9.9	125	1.1	0.01	40
GBS-04-C100A-1-AS-TEM	10	2520/-	1.95	9.9	115	1.1	0.01	40
GBS-04-C100A-1-IS-TEM	10	-/2700	1.95	9.9	115	1.1	0.01	40
GBS-04-C125A-1	13	3100/3330	2.8	17.05	160	2.1	0.01	40
GBS-04-C125A-1-AS	13	4150/-	3.6	17.05	145	2.1	0.01	40

产品选型



产品型号	单指行程 mm	夹持力 N	自重 kg	工件重量 kg	最长手指长度 mm	最大单个手指重量 kg	重复定位精度 mm	IP等级
GBS-04-C240A-1	30	9500/10400	20	55	280	8.5	0.05	40
GBS-04-C240A-1-AS	30	13720/-	24	55	230	8.5	0.05	40
GBS-04-C240A-1-IS	30	-/15170	24	55	230	8.5	0.05	40
GBS-04-C240A-1-SD	30	9500/10400	21.5	55	280	8.5	0.05	64
GBS-04-C240A-1-AS-SD	30	13720/-	25.5	55	230	8.5	0.05	64
GBS-04-C240A-1-IS-SD	30	-/15170	25.5	55	230	8.5	0.05	64
GBS-04-C240A-1-TEM	30	9500/10400	20	55	280	8.5	0.05	40
GBS-04-C240A-1-AS-TEM	30	13720/-	24	55	230	8.5	0.05	40
GBS-04-C240A-1-IS-TEM	30	-/15170	24	55	230	8.5	0.05	40
GBS-04-C300A-1	35	14500/15200	33	79.75	250	11.5	0.05	40
GBS-04-C300A-1-AS	35	21000/-	43.5	79.75	225	11.5	0.05	40
GBS-04-C300A-1-IS	35	-/22700	43.5	79.75	225	11.5	0.05	40
GBS-04-C300A-1-SD	35	14500/15200	35.5	79.75	250	11.5	0.05	64
GBS-04-C300A-1-AS-SD	35	21000/-	46	79.75	225	11.5	0.05	64
GBS-04-C300A-1-IS-SD	35	-/22700	46	79.75	225	11.5	0.05	64
GBS-04-C300A-1-TEM	35	14500/15200	33	79.75	250	11.5	0.05	40
GBS-04-C300A-1-AS-TEM	35	21000/-	43.5	79.75	225	11.5	0.05	40
GBS-04-C300A-1-IS-TEM	35	-/22700	43.5	79.75	225	11.5	0.05	40